

## Arlington 250 litre Combo – CL65

### Assembling the 250 ltr Combo



Remove lid by turning the yellow locking handles through 90°



Using the side handles raise each side panel one at a time.



Make sure each panel is firmly locked into position.



Replace Combo lid after filling and move locking handles into closed position.

### Fitting the Liner



Place folded liner in the bottom of the Combo, ensuring the outlet port on liner is next to the outlet port on Combo.



Move the outlet port on liner towards the outlet port on Combo.



Make sure you locate the clip surrounding the outlet port on liner securely into the Combo's outlet port. Ensure the inlet port is on the top of the liner. Do not unfold the liner. Begin to fill, the only adjustment required during the fill is to ensure the corners of the liners are pulled towards the corners of the box.

### Filling the Combo and Attaching the Coupler



This photograph shows a hose adaptor filling a liner.



Cam adaptor attached.



Attach cam lock to adaptor and secure by lifting the locking arms.



Hose fill adaptor needs to be screwed into cam lock to complete fitting.

Units 16/17  
Salisbury Road Business Park  
Pewsey  
Wiltshire  
SN9 5PZ

Tel: 01672 563723  
Fax: 01672 563733

E: [info@emergencywater.co.uk](mailto:info@emergencywater.co.uk)  
W: [www.emergencywater.co.uk](http://www.emergencywater.co.uk)



## Fitting the Outlet Tap



Outlet port on liner located into outlet port of combo.



Remove cap and fit spout to the port. Checking that the seal has not been broken



When water is require turn orange handle on top of port.

## Security Tags



This photograph shows where the security tag should be placed through the locking handle.



This shows the security tag sealed in place.

## Specifications for the 250 litre Combo 65

External	800 x 600 x 813mm
Internal	740 x 540 x 660
Weight	20kg
Volume	264ltrs

Max Load Stack	
Dynamic (2 High)	700kg
Static (5 High)	1750kg

Material – Polypropylene, food contact approved. Fully recyclable

### Arlington Contacts

Harry Fairbank – Managing Director  
Telephone: 01672 563723  
Mobile: 07860 340983  
Email: [harry@arlingtonpackaging.com](mailto:harry@arlingtonpackaging.com)

Nick Jones – Technical Sales  
Telephone: 01672 563723  
Mobile: 07920 793760  
Email: [nick@arlingtonpackaging.com](mailto:nick@arlingtonpackaging.com)

### Opening Times

Monday	9am – 5pm
Tuesday	9am – 5pm
Wednesday	9am – 5pm
Thursday	9am – 5pm
Friday	9am – 5pm

## Arlington 250 litre Combo

